



EMAR S.R.L.

GLASS WORKING EQUIPMENT

Via del Lavoro, 2B

Tel. +39 - 02 - 90967625

Website: <http://www.emar.it>

20069 Pozzo d'Adda (MI) - Italy

Fax +39 - 02 - 90967628

E-mail: emar@emar.it



HYDRAULIC EXTRUDER FOR TYOKOL LT 200

Mod. M 107

PNEUMATIC FEEDING	: FROM 2 UP TO 8 BAR
VOLTAGE	: 400 Vac. 3 PHASE 50 Hz
TOTAL POWER ASSORBED	: 3 Kw. 400 Vac. 3 PHASE 50 Hz.
EXTRUSION CAPACITY	: 2000 CC/MIN
MIXING RATIO	: FROM 7% UP TO 15%
AIR CONSUMPTION	: 150 NL FOR 2500 cc OF PRODUCT
HEIGHT	: 2500 mm about
LENGTH	: 1200 mm about
WIDTH	: 1400 mm about
WEIGHT	: 640 Kg about

Base component pump with hydraulic feeding. Dosing catalyzer pump with hydraulic feeding. Catalyst pump for pneumatic feeding. Mixing group mechanically connected to the base pump in order to obtain a constant mixing. Different mixing system by means of alpha-mix situated near the gun. Double gasket pressing plate. Revolving over-head swinging arm supporting pipes and mixer. Pressure control of the base and catalyzer components. Hand-operated bleed valves for the product. Automatic pressure relief valve. Fixing brackets for the base drum. All controls with relative adjusting devices are positioned in a single easy to reach panel. Standard thermostat for the adjustment of the base component plate's temperature. Optional thermostat for the adjustment of the base component plate's temperature - washing pump.- Electric control for end material.

Emar srl will reserve the right to modify, at any time, the contents of this catalogue